



1.1nV/ $\sqrt{\text{Hz}}$ Noise, Low Power, Precision Operational Amplifier in Tiny DFN-8 Package

FEATURES

- **LOW-VOLTAGE NOISE:** 1.1nV/ $\sqrt{\text{Hz}}$ at 1kHz
- **100nV_{pp} INPUT VOLTAGE NOISE,** 0.1Hz–10Hz
- **LOW OFFSET VOLTAGE:** 100 μV (max)
- **LOW OFFSET VOLTAGE DRIFT:** 0.2 $\mu\text{V}/^{\circ}\text{C}$ (typ)
- **LOW SUPPLY CURRENT:** 3.6mA/Ch
- **UNITY GAIN STABLE**
- **GAIN BANDWIDTH PRODUCT:** 80MHz (G = 100)
- **SLEW RATE:** 27V/ μs
- **WIDE SUPPLY RANGE:** $\pm 2.25\text{V}$ to $\pm 18\text{V}$, +4.5V to +36V
- **RAIL-TO-RAIL OUTPUT**
- **OUTPUT CURRENT:** 30mA
- **SHUTDOWN:** 20 μA (max)
- **AVAILABLE IN TINY DFN-8 (3x3mm), MSOP-8, SO-8**

APPLICATIONS

- **PLL LOOP FILTER**
- **LOW-NOISE, LOW-POWER SIGNAL PROCESSING**
- **HIGH-PERFORMANCE ADC DRIVERS**
- **HIGH-PERFORMANCE DAC OUTPUT AMPLIFIER**
- **ACTIVE FILTERS**
- **LOW-NOISE INSTRUMENTATION AMPS**
- **ULTRASOUND AMPLIFIERS**
- **PROFESSIONAL AUDIO PREAMPLIFIERS**
- **LOW-NOISE FREQUENCY SYNTHESIZERS**
- **INFRARED DETECTOR AMPLIFIERS**
- **HYDROPHONE AMPLIFIERS**
- **MEDICAL**

DESCRIPTION



The OPA211 series achieves very low 1.1nV/ $\sqrt{\text{Hz}}$ noise density with a supply current of only 3.6mA. It also offers rail-to-rail output swing, which helps to maximize dynamic range.

The OPA211 series' extremely low voltage and current noise, high speed and wide output swing make it an excellent choice as a loop filter amplifier in PLL applications.

In precision data acquisition applications, the OPA211 series of op amps provide <1 μs settling time to 16-bit accuracy even for 10V output swings. This ac performance, combined with only 100 μV of offset and low drift over temperature, make the OPA211 highly suitable for driving fast, high-precision analog-to-digital converters (ADCs) or buffering the outputs of high-resolution digital-to-analog converters (DACs).

The OPA211 is specified over the very wide dual-power supply range of $\pm 2.25\text{V}$ to $\pm 18\text{V}$, or single-supply operation from +4.5V to +36V.

The OPA211 is available in the tiny DFN-8 (3x3mm) and MSOP-8 and SO-8 packages. A dual version, the OPA2211, is available in the DFN-8 (3x3mm) or an MSOP-8 package. This series of op amps is specified from -40°C to $+125^{\circ}\text{C}$.



PRODUCT PREVIEW



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners.



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

ABSOLUTE MAXIMUM RATINGS⁽¹⁾

Over operating free-air temperature range (unless otherwise noted)

	VALUE	UNIT
Supply Voltage	±20	V
Input Voltage	(V ₋) – 0.7 to (V ₊) + 0.7	V
Input Current	±10	mA
Output Short-Circuit ⁽²⁾	Continuous	
Operating Temperature	–55 to +150	°C
Storage Temperature	–65 to +150	°C
Junction Temperature	+150	°C


- (1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not supported.
- (2) Short-circuit to ground, one amplifier per package.

PACKAGE/ORDERING INFORMATION⁽¹⁾

PRODUCT	PACKAGE-LEAD	SINGLE	ENABLE	DUAL	PACKAGE DESIGNATOR	PACKAGE MARKING
Standard Grade						
OPA211A	DFN-8 (3×3mm) ⁽²⁾	ü	ü		DRG	TBD
	MSOP-8 ⁽²⁾	ü	ü		DCK	TBD
OPA211A	SO-8	ü			D	TBD
OPA2211A	DFN-8 (3×3mm) ⁽²⁾			ü	DRG	TBD
	MSOP-8 ⁽²⁾			ü	DCK	TBD
High Grade						
OPA211I	DFN-8 (3×3mm) ⁽²⁾	ü	ü		DRG	TBD
	MSOP-8 ⁽²⁾	ü	ü		DCK	TBD
	SO-8	ü			D	TBD
OPA2211I	DFN-8 (3×3mm) ⁽²⁾			ü	DRG	TBD
	MSOP-8 ⁽²⁾			ü	DCK	TBD

- (1) For the most current package and ordering information see the Package Option Addendum at the end of this document, or see the TI web site at www.ti.com.
- (2) Available Q4, 2007.

PIN CONFIGURATIONS



- (1) NC denotes no internal connection. Pin can be left floating or connected to any voltage between (V-) and (V+).
 (2) Connect thermal die pad to V-.
 (3) Enable function: (V-) ≤ ENABLED ≤ (V+) - 3V; DISABLED ≥ (V+) - 0.35V.

ELECTRICAL CHARACTERISTICS: $V_S = \pm 2.25V$ to $\pm 18V$

BOLDFACE limits apply over the specified temperature range, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$.

At $T_A = +25^\circ\text{C}$ and $R_L = 10k\Omega$, unless otherwise noted.

PARAMETER	CONDITIONS	Standard Grade OPA211A, OPA2211A			High Grade OPA211I, OPA2211I ⁽¹⁾			UNIT
		MIN	TYP	MAX	MIN	TYP	MAX	
OFFSET VOLTAGE								
Input Offset Voltage	V _{OS}	±15V	±20	±100		±20	TBD	μV
Drift	dV _{OS} /dT		0.35	1		0.35		μV/°C
vs Power Supply	PSRR	V _S = ±2.25V to ±18V		2			TBD	μV/V
INPUT BIAS CURRENT								
Input Bias Current	I _B	V _{CM} = 0V	30	150		30	TBD	nA
Over Temperature			TBD	TBD		TBD	TBD	nA
Offset Current	I _{OS}	V _{CM} = 0V	10	100		10	TBD	nA
Over Temperature			TBD	TBD		TBD	TBD	nA
NOISE								
Input Voltage Noise:	e _n							
f = 0.1Hz to 10Hz			0.1			0.1		μV _{PP}
Voltage Noise Density:								
f = 10Hz			2.5			2.5		nV/√Hz
f = 100Hz			1.6			1.6		nV/√Hz
f = 1kHz			1.1			1.1		nV/√Hz
Input Current Noise Density:	i _n							
f = 10Hz			TBD			TBD		pA/√Hz
f = 1kHz			1.5			1.5		pA/√Hz
INPUT VOLTAGE RANGE								
Common-Mode Voltage Range	V _{CM}		(V–)+1.8	(V+)-1.4	(V–)+1.8		(V+)-1.4	V
Common-Mode Rejection Ratio	CMRR	(V–)+1.8V < V _{CM} < (V+)-1.4V	114	120	114	120		dB
INPUT IMPEDANCE								
Differential			10 ¹⁰ TBD			10 ¹⁰ TBD		Ω pF
Common-Mode			10 ⁹ 2			10 ⁹ 2		Ω pF
OPEN-LOOP GAIN								
Open-Loop Voltage Gain	A _{OL}	(V–)+0.2V < V _O < (V+)-0.2V, R _L = 10kΩ	114	120	114	120		dB
	A _{OL}	(V–)+0.6V < V _O < (V+)-0.6V, R _L = 600Ω	110	114		114		dB
Over Temperature		(V–)+0.6V < V _O < (V+)-0.6V, R _L = 600Ω, I _O < 25mA	110	114	110	114		dB
FREQUENCY RESPONSE								
Gain-Bandwidth Product	GBW	G = 100	80			80		MHz
		G = 1	58			58		MHz
Slew Rate	SR		27			27		V/μs
Settling Time, 0.01%	t _S	G = –1, 10V Step, C _L = 100pF	TBD			TBD		μs
0.0015% (16-bit)		G = –1, 10V Step, C _L = 100pF	TBD			TBD		μs
Overload Recovery Time		G = –1	< 1			< 1		μs
Total Harmonic Distortion + Noise	THD+N	G = +10, f = 20kHz, V _O = 20V _{PP} , 600Ω	TBD			TBD		%

(1) Shaded cells indicate different specifications from low-grade version of device.

ELECTRICAL CHARACTERISTICS: $V_S = \pm 2.25V$ to $\pm 18V$ (continued)

BOLDFACE limits apply over the specified temperature range, $T_A = -40^\circ\text{C}$ to $+125^\circ\text{C}$.

At $T_A = +25^\circ\text{C}$ and $R_L = 10k\Omega$, unless otherwise noted.

PARAMETER		CONDITIONS	Standard Grade OPA211A, OPA2211A			High Grade OPA211I, OPA2211I ⁽¹⁾			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
OUTPUT									
Voltage Output	V _{OUT}	R _L = 10kΩ, A _{OL} > 114dB R _L = 600Ω, A _{OL} > 110dB R _L = 600Ω, A _{OL} > 110dB, I _O < 25mA	(V–)+0.2 (V–)+0.6 (V–)+0.6	 +30/–45	(V+)-0.2 (V+)-0.6 (V+)-0.6	(V–)+0.2 (V–)+0.6 (V–)+0.6	 +30/–45	(V+)-0.2 (V+)-0.6 (V+)-0.6	V V V
Short-Circuit Current	I _{SC}								mA
Capacitive Load Drive	C _{LOAD}		See Typical Characteristics			See Typical Characteristics			pF
POWER SUPPLY									
Specified Voltage	V _S		±2.25		±18	±2.25		±18	V
Quiescent Current (per channel)	I _Q	I _{OUT} = 0		3.6	TBD		3.6	TBD	mA
Over Temperature				TBD	TBD		TBD	TBD	mA
Shutdown Current		Disabled		TBD	20		TBD	20	μA
ENABLE Pin Input Voltage		Enabled			(V+)-3			(V+)-3	V
ENABLE Pin Input Voltage		Disabled	(V+)-0.35			(V+)-0.35			V
TEMPERATURE RANGE									
Specified Range			-40		+125	-40		+125	°C
Operating Range			-55		+150	-55		+150	°C
Thermal Resistance	θ _{JA}								
DFN (3mm × 3mm)		Soldered to approximately 5cm × 5cm copper area		65			65		°C/W
SO-8, MSOP-8				150			150		°C/W

PACKAGING INFORMATION

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/Ball Finish	MSL Peak Temp ⁽³⁾
OPA211AID	PREVIEW	SOIC	D	8	75	TBD	Call TI	Call TI
OPA211AIDGKR	PREVIEW	MSOP	DGK	8	2500	TBD	Call TI	Call TI
OPA211AIDGKT	PREVIEW	MSOP	DGK	8	250	TBD	Call TI	Call TI
OPA211AIDR	PREVIEW	SOIC	D	8	2500	TBD	Call TI	Call TI
POPA211AID	PREVIEW	SOIC	D	8	75	TBD	Call TI	Call TI

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBsolete: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

DGK (S-PDSO-G8)


PLASTIC SMALL-OUTLINE PACKAGE



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 per end.
 - D. Body width does not include interlead flash. Interlead flash shall not exceed 0.50 per side.
 - E. Falls within JEDEC MO-187 variation AA, except interlead flash.

D (R-PDSO-G8)

PLASTIC SMALL-OUTLINE PACKAGE



4040047-2/H 11/2006

NOTES:

- A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 (0,15) per end.
D. Body width does not include interlead flash. Interlead flash shall not exceed .017 (0,43) per side.
E. Reference JEDEC MS-012 variation AA.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DSP	dsp.ti.com
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
Low Power Wireless	www.ti.com/lpw

Applications

Audio	www.ti.com/audio
Automotive	www.ti.com/automotive
Broadband	www.ti.com/broadband
Digital Control	www.ti.com/digitalcontrol
Military	www.ti.com/military
Optical Networking	www.ti.com/opticalnetwork
Security	www.ti.com/security
Telephony	www.ti.com/telephony
Video & Imaging	www.ti.com/video
Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265